






# ELIPSOIDAL • PAR • BLINDER

UNIT	ELP CL 36°	Rush PAR 2 Zoom (RGBW)	LED PAR Zoom (RGBW)	LED PAR (RGBW)	LED Blinder
					
<b>ELECTRICAL</b>	230v,50Hz : 249w	230v,50Hz :148w	230v,50Hz :400 w	230v,50Hz :120 w	230v,50Hz :850 w
<b>LAMP</b>	91x RGBAL LED	12x 10w RGBW LED	7x 40w RGBW LED	36x 3w RGBW LED	4x 200wWW LED
Type	91x RGBAL LED	12x 10w RGBW LED	7x 40w RGBW LED	36x 3w RGBW LED	4x 200wWW LED
Average life time	30000hours	50000hours	50000hours	50000hours	100000hours
Color temperature					
Lumens / Lux					
<b>PHYSICAL</b>	648mm * 259mm * 254mm	266mm * 287mm * 329mm	296mm * 220mm * 436mm	260mm * 200mm * 270mm	393mm * 376mm * 210mm
Dimensions ( Length, Wide, Height)	648mm * 259mm * 254mm	266mm * 287mm * 329mm	296mm * 220mm * 436mm	260mm * 200mm * 270mm	393mm * 376mm * 210mm
Weight	7.7kg	5.5kg	6.8kg	4kg	13kg
<b>CONTROL</b>	1ch / 10ch / 17ch	5ch / 9ch	11ch	6ch	2ch / 6ch / 12ch
DMX channels	1ch / 10ch / 17ch	5ch / 9ch	11ch	6ch	2ch / 6ch / 12ch
DMX data in,out	XLR 5pin	XLR 5pin	XLR 3pin	XLR 3pin	XLR 3pin
<b>DIYNAMIC</b>	Manual (Tilt)	240° (Tilt)	Manual (Tilt)	Manual (Tilt)	Manual (Tilt)
Pan, Tilt	Manual (Tilt)	240° (Tilt)	Manual (Tilt)	Manual (Tilt)	Manual (Tilt)
Zoom range	36°	10° - 60°	2°~50°	25°	00
Color mixing	RGBAL	RGBW	RGBW	RGBW	Warm, White
Color wheel	Not	Not	Not	Not	Not
CTO / CTB	Not	Not	Not	Not	Not
Shape / Barndoor	Not	Not	Not	Not	Not