

## **OPTIC**

---

- LED: 16 × 40W RGBW LED
- Beam angle: 4 ~ 37°
- Field angle: 9 ~ 41°
- Lifetime: 50000 H

## **EFFECT**

---

- All kinds of built-in program for your option
- Strobe: 1 ~ 20Hz
- Dimmer: 5kinds

## **SOFTWARE**

---

- Via USB & DMX signal to update
- Intelligent temperature protection to ensure LED service life

## **CONTROL & PROGRAM**

---

- Channel: 16/18/78CH
- Protocol: DMX512, RDM, ARTNET/KLINGNET
- Data connector: 5PIN XLR, RJ45
- Display: OLED display

## **TILT MOVEMENT**

---

- Tilt: 240° ( 8bit/16bit precision scanning)

## **HOUSING**

---

- Aluminum alloy structure + plastic (VO)
- Fan cooling

## **POWER CONSUMPTION**

---

- Voltage: AC 110V ~ 240V 50/60Hz
- Rated power: 730 W

## **OTHER**

---

- IP rating: IP30
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

## **SIZE & WEIGHT**

---

- Size: 1068 × 150 × 291 mm
- N.W: 23.5 kgs