

LED Moving Head Series



- Optic**
 - LED: 25 x 15W 4in1 RGBW LED
 - Beam angle: 4°
 - Field angle: 18°
 - Average lifetime: ≥50000H
- Pan&tilt movement angle**
 - Pan &Tilt infinite rotation(8bit/16bit precision scanning)
- Color**
 - Homogeneous RGBW macros color and wonderful rainbow effect
 - Can creat unlimited movement feeling and infinite all kinds of colr changes
- Effect**
 - 9 built-in program and 27 graph for your option
 - Fast electric strobe 1 – 20 Hz
 - Dimmer mode:2kinds
 - Dimmer curve:4 kinds
- Control and Program**
 - DMX Channel mode: 15/17/19CH
 - Protocol: DMX512, RDM, ARTNET/KLINGNET
 - Data connector:3PIN/5PIN XLR DMX in/out, RJ45 network in/out

- Display : 1.8inches touch screen, the operation panel has a rechargeable battery that allows you to access the menu to set the address code and make other settings without power on
- Humanized display mode, press the "UP" key under the DMX interface can quickly make the display 180 ° reverse
- Software**
 - Software updated: via DMX signal to update software, more convenient and faster
 - Silent fan, intelligence adjust speed
 - Auto temperature control when overheating make sure LED life time longer
- Structure**
 - Aluminium alloy + Plastic shell (VO)
- Power consumption**
 - Voltage : AC 100V-240V 50/60Hz
 - Rated power : 420W
- other**
 - IP rating: IP 30
 - Work environment: -5 C-45 C
- Size and Weight**
 - Size: 480mm x 260mm x 584mm
 - NW: 18.6kg



M2515

25pcs 15W RGBW 4in1 LED Source, beam angle is 4°. Each light source can be controlled independently. The dynamic graphics can be projected in 3D space. Pan&Tilt can be rotated infinitely. Except DMX control, it still have the powerful RDM control and ARTNET/KLINGNET technology. with strong dynamic multi-directional beam, Can create a brilliant lighting graphics effect.

